



PRODUCT SPECIFICATION

AISCAN BGE

TYPE	COMPOSITION	Ø OUT mm	TOLER ANCE. mm	Ø INS. mm	LENGTH m	TOLER. mm	SLEEVES	LABELS	TUBES MALLET	Nº TIES
AISCAN-BGE-16	RIGID PVC	16	+0 -0,3	10,5	3000	+10 -5	1	1	19	3
AISCAN-BGE-20	RIGID PVC	20	+0 -0,3	14	3000	+10 -5	1	1	19	3
AISCAN-BGE-25	RIGID PVC	25	+0 -0,4	18	3000	+10 -5	1	1	19	3
AISCAN-BGE-32	RIGID PVC	32	+0 -0,4	24,5	3000	+10 -5	1	1	10	3
AISCAN-BGE-40	RIGID PVC	40	+0 -0,4	31,5	3000	+10 -5	1	1	10	3
AISCAN-BGE-50	RIGID PVC	50	+0 -0,5	40,5	3000	+10 -5	1	1	5	3
AISCAN-BGE-63	RIGID PVC	63	+0 -0,6	52	3000	+10 -5	1	1	5	3
EDITION DATE	EDITION NUMBER	CARD NUMBER								
2015/09	5	EP-BGEM								



CHARACTERISTICS ACCORDING TO STANDARD IEC 61386-21		CHARACTERISTICS LABEL <i>Each label indicates:</i>	ACCESORY TUBE
CODE:	432112540010	Type, nominal, number of meter, standard UNE-EN applied, "CE" marked, storage and use instructions, Bar code EAN-13, date, control number and manufacture line.	TYPE "AISCAN-B" WICH PLUGS IN C/GREY
CRUSHING STRENG:	>1250 N		
IMPACT RESISTANCE:	>2J at -5°C	EACH TUBE BAR INDICATES: type, nominal, standard UNE-EN applied, code, date, hour, manufacture line and "CE" marked.	
OPERATING TEMPERATURE RANGE:	-5+60°C		
RIGID	YES		
DIELECTRICAL RIGIDITY:	>2000 V		
ISOLATION RESISTANCE:	>100 MOhm		
EXTERNAL INFLUENCES:	IP54		
FLAME PROPAGATE:	NO		
COLOUR:	GREY RAL. 7035		

- NO CONTROLLED COPY. THIS INFORMATION COULD BE MODIFIED BY AISCAN WHITOUT PREVIOUS ADVERTISMENT-