




PRODUCT SPECIFICATION

AISCAN BMPG - 35

TYPE	MATERIAL	COATING	A	B	ALLOWABLE WORKING LOAD (N/m)	PACKING (meters)	PLAIN
AISCAN-BMPG-310	METALLIC	HOT DIP GALVANISED	100	35	388	12	
AISCAN-BMPG-315	"	"	150	35	293	12	
AISCAN-BMPG-320	"	"	200	35	435	12	
AISCAN-BMPG-330	"	"	300	35	411	6	
EDITION DATE	EDITION NUMBER	CARD NUMBER					
2013/10	2	EP-BMPG 35					

CHARACTERISTICS ACCORDING TO STANDARD IEC 61537:2006

DESCRIPTION:	MESH CABLE TRAY HOT DIP GALVANISED.
COATING:	HOT DIP GALVANISED IN ACCORDING TO UNE-EN ISO 1461:2010
MATERIAL:	METALLIC
ELECTRICAL CONTINUITY:	YES
FLAME PROPAGATE:	NO
OPERATING TEMPERATURE RANGE:	-40 °C / 150 °C
RESISTANCE TO CORROSION:	TYPE 6
IMPACT RESISTANCE:	20 J TO -40 °C
ALLOWABLE WORKING LOAD (CTA):	DISTANCE BETWEEN SUPPORTS (1,5 METERS)

OBSERVATIONS

FOR THE UNION BETWEEN BRACKETS WILL BE REQUIRED THE USE OF 2 TO 4 SETS OF UNION (CUBS), DEPENDING THE WIDTH OF THE TRAY.

WITH ALL EDGES ROUNDED.

ACCESORIOS

TRAY ATTACHMENT ASSEMBLY (CUB)
UNIVERSAL MESH CABLE TRAY COVER (TUBC)
OMEGA BRACKET (SO)

THE INSTALLATION OF THIS PRODUCT WILL BE CARRIED OUT ACCORDING TO THE R.E.B.T.