



PRODUCT SPECIFICATION

AISCAN BNR

TYPE	COMPOSITION	Ø OUT mm	TOLER. ANCE. mm	Ø INS. mm	LENGTH m	TOLER. mm	THREAD	THREAD LENGTH MM.	SLEEVES	LABELS	TUBES MALLET	Nº TIES
AISCAN-BNR-16	RIGID PVC	16	+0 -0,3	10,5	3000	+10 -5	M16X1,5	12,5 +3-0	1	1	19	3
AISCAN-BNR-20	RIGID PVC	20	+0 -0,3	14	3000	+10 -5	M20X1,5	14 +3-0	1	1	19	3
AISCAN-BNR-25	RIGID PVC	25	+0 -0,4	18	3000	+10 -5	M25X1,5	17 +3-0	1	1	19	3
AISCAN-BNR-32	RIGID PVC	32	+0 -0,4	24,5	3000	+10 -5	M32X1,5	19 +3,5-0	1	1	10	3
AISCAN-BNR-40	RIGID PVC	40	+0 -0,4	31,5	3000	+10 -5	M40X1,5	21 +4-0	1	1	10	3
AISCAN-BNR-50	RIGID PVC	50	+0 -0,5	40,5	3000	+10 -5	M50X1,5	23 +4,5-0	1	1	5	3
AISCAN-BNR-63	RIGID PVC	63	+0 -0,6	52	3000	+10 -5	M63X1,5	25 +4,5-0	1	1	5	3
EDITION DATE	EDITION NUMBER	CARD NUMBER										
2014/05	4	EP-BNRM										

CHARACTERISTICS ACCORDING TO STANDARD IEC 61386-21	
CODE:	432112540010
CRUSHING STRENGTH:	>1250 N
IMPACT RESISTANCE:	>2J at -5°C
OPERATING TEMPERATURE RANGE:	-5+60°C
RIGID	YES
DIELECTRICAL RIGIDITY:	>2000 V
ISOLATION RESISTANCE:	>100 MOhm
EXTERNAL INFLUENCES:	IP54
FLAME PROPAGATE:	NO
COLOUR:	BLACK

CHARACTERISTICS LABEL <i>Each label indicates:</i>
Type, nominal, number of meter, standard UNE-EN applied, "CE" marked, storage and use instructions, Bar code EAN-13, date, control number and manufacture line.
EACH TUBE BAR INDICATES: type, nominal, standard UNE-EN applied, code, date, hour, manufacture line and "CE" marked."

ACCESORY TUBE
TYPE "AISCAN-B" THREADBLE C/BLACK

- NO CONTROLLED COPY. THIS INFORMATION COULD BE MODIFIED BY AISCAN WHITOUT PREVIOUS ADVERTISMENT-