



PRODUCT SPECIFICATION

HORIZONTAL ELBOW 90°



G.S.	Δ (kg/m)	G.C.	Δ (kg/m)**	A (mm)	⌋ (uni.)
CH9S0310	0,55	CH9G0310	0,60	100	1
CH9S0315	0,81	CH9G0315	0,89	150	1
CH9S0320	0,96	CH9G0320	1,06	200	1
CH9S0330	1,88	CH9G0330	2,05	300	1
CH9S0610	0,88	CH9G0610	0,73	100	1
CH9S0615	0,85	CH9G0615	0,93	150	1
CH9S0620	1,12	CH9G0620	1,24	200	1
CH9S0630	1,73	CH9G0630	1,91	300	1
CH9S0640	3,01	CH9G0640	3,31	400	1
CH9S0650	3,37	CH9G0650	3,70	500	1
CH9S0660	5,14	CH9G0660	5,65	600	1
CH9S0810	0,70	CH9G0810	0,76	100	1
CH9S0815	0,94	CH9G0815	1,04	150	1
CH9S0820	1,23	CH9G0820	1,35	200	1
CH9S0830	1,88	CH9G0830	2,06	300	1
CH9S0840	3,12	CH9G0840	3,43	400	1
CH9S0850	4,16	CH9G0850	4,68	500	1
CH9S0860	5,48	CH9G0860	6,02	600	1
CH9S1010	0,85	CH9G1010	0,94	100	1
CH9S1015	1,05	CH9G1015	1,15	150	1
CH9S1020	1,50	CH9G1020	1,65	200	1
CH9S1030	2,02	CH9G1030	2,22	300	1
CH9S1040	2,82	CH9G1040	3,10	400	1
CH9S1050	3,75	CH9G1050	4,12	500	1
CH9S1060	5,74	CH9G1060	6,31	600	1

EDITION DATE

EDITION N°

2016/06

1

**ACCORDING TO
UNE-EN 61537-2007**

SENDIZIMIR GALVANISATION ACCORDING TO UNE-EN 10346:2010.
HOT DIP GALVANISED ACCORDING TO UNE-EN ISO 1461:2010

CHARACTERISTICS OF INSTALLATION

THE INSTALLATION OF THIS PRODUCT WILL BE CARRIED OUT
ACCORDING TO THE R.E.B.T.

- COPY NO CONTROLLED. THIS INFORMATION COULD BE MODIFIED BY AISCAN WITHOUT PREVIOUS NOTICE.