



PRODUCT SPECIFICATION

THREADED METAL CURVE -180°

TYPE	COMPOSITION	Ø OUT mm	TOLERANCE mm	Ø INS. mm	LENGTH mm	TOLER. mm	INS. RADIUS (+2)	ANG.º	+ - ANGº	THREAD LENGTH +1	CURVES/ BOX
AISCAN-CMR180-32	STEEL	32,5	+0 -0,4	29,2	220	+5	145	180	3	20	5
AISCAN-CMR180-40	"	40	+0 -0,4	37,5	270	+5	165	180	3	22	5
AISCAN-CMR180-50	"	50	+0 -0,4	47,2	325	+5	185	180	3	30	5
EDITION DATE	EDITION NUMBER	CARD NUMBER									
2009/02	2	EP-CMR180									

CHARACTERISTICS ACCORDING TO STANDARD UNE-EN 61386-21

CODE:	555711542010
CRUSHING STRENG:	>4000 N
IMPACT RESISTANCE:	>20,4J at -45°C
OPERATING TEMPERATURE RANGE:	-45+400°C
RIGID:	YES
CORROSION RESISTANCE:	MEDIUM
FLAME PROPAGATE:	NO
COLOUR:	ZINC
NOT CORROSIVE INTERIOR PAINT	

CHARACTERISTICS LABEL

Each label indicates:

Each curve specifies the type, nominal, CE marking, date and hour

USE

IN THE TUBE TYPE: "AISCAN-TMR"

- NO CONTROLLED COPY. THIS INFORMATION COULD BE MODIFIED BY AISCAN WHITOUT PREVIOUS ADVERTISMENT.-