



PRODUCT SPECIFICATION

AISCAN FHF

TYPE	COMPOSITION	Ø OUT mm	TOLER- ANCE mm	Ø INS. mm	LENGTH m	TOLER. mm	Nº SPIRAL	SPIRAL SEQUENCE	LAYERS	RADIUS MIN. CURVAT URE mm	Nº TIES
AISCAN-FHF-20	HALOGEN FREE TERMOPLASTIC	20,5	+0,5	13,4	100	+2 -1	72	8-8-8-8-8-8-8-8	9	60	4
AISCAN-FHF-25	“	25,5	+0,5	18,5	75	+2 -1	56	8-8-8-8-8-8-8	7	75	4
AISCAN-FHF-32	“	32,5	+0,5	24,3	50	+2 -1	39	7-6-7-6-7-6	6	96	4
AISCAN-FHF-40	“	40,5	+0,5	31,2	25	+1 -0,5	20	5-5-5-5	4	160	4
EDITION DATE	EDITION NUMBER	CARD NUMBER									
2014/05	5	EP-FHFM									

CHARACTERISTICS ACCORDING TO STANDARD IEC 61386-22

CODE:	232122540010
CRUSHING STRENG:	>320 N
IMPACT RESISTANCE:	>2J at -5°C
OPERATING TEMPERATURE RANGE:	-5+60°C
CURVABLE	YES
EXTERNAL INFLUENCES:	>2000 V
FLAME PROPAGATE:	>100 MOhm
COLOUR:	IP54
CODE:	NO
CRUSHING STRENG:	GREY

CHARACTERISTICS LABEL

Each label indicates:

Type, nominal, number of meter, standard UNE-EN applied, "CE" marked, storage and use instructions, Bar code EAN-13, date, control number and manufacture line.

ACCORDING TO STANDARD UNE-EN 50267-2-2 [old UNE-21-147(2)/IEC-754(2)] about "Determination of the degree of acidity of gases for materials by measuring pH and conductivity".
ACCORDING TO STANDARD UNE-EN 21031-15:2008 "Determination of halogens. Elementary test".

- NO CONTROLLED COPY. THIS INFORMATION COULD BE MODIFIED BY AISCAN WHITOUT PREVIOUS ADVERTISMENT.-