



PRODUCT SPECIFICATION

AISCAN-RHF SLEEVES

TYPE	COMPOSITION	Ø OUT mm	TOLER. mm	LENGTH mm	TOLER. mm	THREAD IN ACCORDING TO UNE-EN 60423	COLOUR
AISCAN-MR-16	HALOGEN-FREE RIGID TERMOPLASTIC	19,7	+0,2	30,8	+0,3	M16X1,5	GREY
AISCAN-MR-20	“	23,85	+0,2	33,65	+0,3	M20X1,5	“
AISCAN-MR-25	“	29,8	+0,2	39,6	+0,3	M25X1,5	“
AISCAN-MR-32	“	36,9	+0,2	44,5	+0,4	M32X1,5	“
AISCAN-MR-40	“	46,9	+0,2	50	+0,4	M40X1,5	“
AISCAN-MR-50	“	56,8	+0,2	54,7	+0,5	M50X1,5	“
AISCAN-MR-63	“	70,6	+0,2	60,3	+0,5	M63X1,5	“
EDITION DATE	EDITION NUMBER	CARD NUMBER					
2007/12	2	EP-M-RHF					

ACCORDING TO STANDARD UNE-EN 50267-2-2 [old UNE-21-147(2)/IEC-754(2)] about "Determination of the degree of acidity of gases for materials by measuring pH and conductivity".
ACCORDING TO STANDARD UNE-EN 21031-15:2008 "Determination of halogens. Elementary test".

- **THESE ACCESSORIES ARE USED FOR THE TUBES "AISCAN-RHF"**
- **MINIMUM INSIDE DIAMETER IN ACCORDING TO UNE-EN 60423 (TABLE 1 – Cota D¹min)**

- NO CONTROLLED COPY. THIS INFORMATION COULD BE MODIFIED BY AISCAN WHITOUT PREVIOUS ADVERTISMENT-