




PRODUCT SPECIFICATION

RAIL 41 X 21 SENDZIMIR

| TYPE | MATERIAL | COATING | A | THICKNESS (mm.) | PACKING (Units) | PLAIN |
|------------------|-----------------------|-------------|------|-----------------|-----------------|---|
| AISCAN- R4121S05 | STEEL DX51D+ZF 200MAC | SENDZIMIR | 500 | 2 | 8 |  |
| AISCAN- R4121S10 | " | " | 1000 | 2 | 4 | |
| AISCAN- R4121S20 | " | " | 2000 | 2 | 2 | |
| 2012/11 | 1 | EP – R4121S | | | | |

| CHARACTERISTICS ACCORDING TO STANDARD IEC 61537:2007 | | OBSERVATION: |
|--|---|--|
| DESCRIPTION: | RAIL 41 X 21. | THE INSTALLATION OF THIS PRODUCT WILL BE CARRIED OUT ACCORDING TO THE R.E.B.T. |
| MATERIAL: | STEEL DX51D+ZF 200MAC | |
| COATING: | SENDZIMIR GALVANISED ACCORDING STANDARD UNE-EN ISO 10346:2010 | |
| MATERIAL: | METALLIC | |
| ELECTRICAL CONTINUITY: | YES | |
| FLAME PROPAGATION: | NO | |
| OPERATING TEMPERATURE RANGE: | -50 °C / 150 °C | |
| RESISTANCE TO CORROSION: | CLASS 3 | |

- COPY NOT CONTROLLED. THIS INFORMATION CAN BE MODIFIED BY AISCAN WITHOUT PREVIOUS NOTICE -