



PRODUCT SPECIFICATION

AISCAN REXA-E

TYPE	COMPOSITION	Ø OUT mm	TOLER- ANCE. mm	Ø INS. mm	LENGTH m	TOLER. mm	SLEEVES	LABELS	TUBES MALLET	Nº TIES
AISCAN-REXAE-20	PVC + MAT. ANTI.V	20	+0 -0,3	14	3000	+10 -5	1	1	19	3
AISCAN-REXAE-25	“	25	+0 -0,4	18	3000	+10 -5	1	1	19	3
AISCAN-REXAE-32	“	32	+0 -0,4	24,5	3000	+10 -5	1	1	10	3
AISCAN-REXAE-40	“	40	+0 -0,4	31,5	3000	+10 -5	1	1	10	3
AISCAN-REXAE-50	“	50	+0 -0,5	40,5	3000	+10 -5	1	1	5	3
AISCAN-REXAE-63	“	63	+0 -0,6	52	3000	+10 -5	1	1	5	3
EDITION DATE	EDITION NUMBER	CARD NUMBER								
2014/05	3	EP-REXA-E								

CHARACTERISTICS ACCORDING TO STANDARD IEC 61386-21	
CODE:	432112540010
CRUSHING STRENGTH:	>1250 N
IMPACT RESISTANCE:	>2J at -5°C
OPERATING TEMPERATURE RANGE:	-5+60°C
RIGID	YES
DIELECTRICAL RIGIDITY:	>2000 V
ISOLATION RESISTANCE:	>100 MOhm
EXTERNAL INFLUENCES:	IP54
FLAME PROPAGATE:	NO
COLOUR:	GREY RAL 7037

CHARACTERISTICS LABEL
<i>Each label indicates:</i>
Type, nominal, number of meter, standard UNE-EN applied, “CE” marked, storage and use instructions, Bar code EAN-13, date, control number and manufacture line.
EACH TUBE BAR INDICATES: type, nominal, standard UNE-EN applied, code, date, hour, manufacture line and “CE” marked.”

ACCESORY TUBE
TYPE “AISCAN-REXA-E” WICH PLUGS IN C/DARK GREY

- NO CONTROLLED COPY. THIS INFORMATION COULD BE MODIFIED BY AISCAN WHITOUT PREVIOUS ADVERTISMENT-