

PRODUCT SPECIFICATION

RAIL "U" 41 X 35 SENDZIMIR

ТҮРЕ	MATERIAL	COATING	A	THICKNESS (mm.)	PACKING (Units)
AISCAN- RU4135S05	STEEL DX51D+ZF 200MAC	SENDZIMIR	500	2	8
AISCAN- RU4135S10	N	w	1000	2	4
AISCAN- RU4135S20	W	w.	2000	2	2
2017/01	1	EP – RU4135S	•		

CI		
DESCRIPTION:	RAIL "U" 41 X 35.	OBSERVATION:
MATERIAL:	STEEL DX51D+ZF 200MAC	THE INSTALLATION OF THIS PRODUCT WILL BE CARRIED OUT ACCORDING TO THE R.E.B.T.
COATING:	SENDZIMIR GALVANISED ACCORDING STANDARD UNE-EN ISO 10346:2010	
MATERIAL:	METALLIC	
ELECTRICAL CONTONUITY:	YES	
FLAME PROPAGATION:	NO	
OPERATING TEMPERATURE RANGE:	-50 °C / 150 °C	
RESISTANCE TO CORROSION:	CLASS 3	

- COPY NOT CONTROLLED. THIS INFORMATION CAN BE MODIFIED BY AISCAN WITHOUT PREVIOUS NOTICE -