



# PRODUCT SPECIFICATION

## "U" MULTIFUNCTION OMEGA BRACKET (SENDZIMIR)

TYPE	MATERIAL	COATING	A	ALLOWABLE WORKING LOAD (N/m)	PACKING (Units)	PLAIN
AISCAN-SOUMS 10	METALLIC	SENDZIMIR GALVANISED	100	491	4	
AISCAN-SOUMS15	"	"	150	706	4	
AISCAN-SOUMS20	"	"	200	573	4	
AISCAN-SOUMS30	"	"	300	428	4	
EDITION DATE	EDITION NUMBER	DOCUMENT ID.				
2016/01	1	EP - SOUMS				

### CHARACTERISITCS ACCORDING TO STANDARD IEC 61537:2007

DESCRIPTION:	SENDZIMIR GALVANISED "U" MULTIFUNCTION OMEGA BRACKET
COATING:	SENDZIMIR GALVANISED IN ACCORDING TO UNE-EN ISO 10346:2010
MATERIAL:	METALLIC
ELECTRICAL CONTINUITY:	YES
FLAME PROPAGATE:	NO
OPERATING TEMPERATURE RANGE:	-40 °C / 150 °C
RESISTANCE TO CORROSION:	TYPE 3
IMPACT RESISTANCE:	20 J TO -40 °C

### OBSERVATIONS

THE INSTALLATION OF THIS PRODUCT WILL BE CARRIED OUT ACCORDING TO THE R.E.B.T.