

Hoja de características del producto

Especificaciones



Licencia profesional de grupo de tiempo de construcción, operador de EcoStruxure Terminal Expert, digital

HMIPELCZLGPAZZ

Principal

Gama De Producto	EcoStruxure Operator Terminal Expert
Tipo De Producto O Componente	Licencia
Formato	Digital
Tipo De Software	Professional
Tipo De Licencia	Node locked license
Variante	Buildtime
Versión Del Software	V3.5
Operating System Requirement	Windows 10 64 bit
Requisitos Del Sistema	8 GB RAM 30 GB hard-drive space
Idioma De Usuario	Inglés Italiano Chino Español Francés Alemán Portugués Coreano

Complementario

Tipo De Licencia	Permanent
------------------	-----------

Aviso Legal: Esta documentación no pretende sustituir ni debe utilizarse para determinar la adecuación o la fiabilidad de estos productos para aplicaciones específicas de los usuarios

Communication Port Protocol	CANopen slave Couzet Automation millenium 3 FBD Emerson Industrial Automation Modbus SIO master Control Techniques Modbus SIO master Emerson Process Management ROC Plus Ethernet Emerson Process Management ROC SIO HTTP IPsec Mitsubishi A series Ethernet Mitsubishi FX series CPU direct Mitsubishi FX series Ethernet Mitsubishi iQ-R/F series Ethernet SLMP client Mitsubishi Q series CPU direct Mitsubishi Q series QnU CPU Ethernet Mitsubishi Q/QnA series serial Modbus Organization Modbus SIO ASCII master Modbus Organization Modbus SIO master Modbus Organization Modbus SIO slave Modbus Organization Modbus TCP master Modbus Organization Modbus TCP slave Omron CS/CJ/CP series host link Omron CS/CJ/CP/NX series Ethernet Omron CS/CJ/NJ/NX series Ethernet/IP OPC UA server Profibus DP slave Rockwell Automation Ethernet/IP Rockwell Automation DF1 Rockwell Automation DH485 Schneider Electric Modbus SIO master Schneider Electric Modbus TCP master Schneider Electric Modbus TCP master via USB Schneider Electric Machine expert network Schneider Electric PacDrive Schneider Electric Uni-Telway Schneider Electric Zelio Logic Siemens Simatic S7 Ethernet Siemens Simatic S7 MPI direct Siemens TIA portal Ethernet websocket
Versión Anterior Del Software	V3.4
Función De Software	Professional screen design Simulation Alarms and events Blocky script Convertors Dockable windows interface environment Export with CSV and tab delimiter Import with CSV and tab format Data and operation logging Multi language development Multi language tables Object binding and properties Target binding and properties Project transfer (Ethernet, filesystem, USB cable) Recipes Screens (contents and folders) Security (levels, project, users) Project and application settings System keypad Text script Color themes Variable (arrays, binding, properties, structures) Online and integrated help system OPC UA Server Web server API
Compatibilidad De Gama	Harmony GTU Harmony GTW Harmony STM6 Harmony STO Harmony STO & STU Harmony P6
Opción De Alojamiento	On-premise
Tamaño De La Licencia	Group (3 station)

Processor Requirement	Intel core i3 8th generation
	Intel core i5 8th generation
Display Resolution (**)	1280 x 720 pixels HD